



## Mercury SX362IR 2MP Dome Vari focal Network Camera



### Key Features

- 1/2.7" Progressive Scan CMOS
- 1920 × 1080 @ 30fps WDR (2MP)
- ONVIF Profile S/ G/ Q/ T support
- Multi Codec support (H.265/ H.264/ MJPEG)
- HDR Engine Gen3
- 3D DNR
- All Aluminium Housing
- IP67, IK10
- IR LED (working distance up to 40m)
- POE (IEEE 802.3af)
- 4 year Warranty

### Multi Codec

The Mercury SX362, incorporates the latest innovations in codec technology offering the ability to stream in either H.264 or the new H.265 format enabling you to reduce your video storage requirements if you choose H.265.

### 2.7-12mm Motorised Lens

The Mercury SX362 comes with a new motorised 2.7-12mm lens offering a larger range of scene capturing capabilities making this camera suitable for even more applications. The remote zoom and focus feature enables convenient focusing over the network together with the special P-Iris lens, eliminating the need for hands-on fine tuning. This remote adjustment functionality greatly speeds up installation time and reduces total cost to the project.

### HDR Engine Gen3

The latest HDR engine delivers excellent, natural high dynamic images. Both details of high light and low light areas are kept, and no blending artifacts are generated.

## Specifications

Camera	
Camera Type	Dome day / night (ICR Type)
Effective Pixels	1920 (H) x 1080(V) (2MP)
Pixel Size	2.0 μm
Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	0.08 lux (Colour)/ 0.008 lux (B/W)
Shutter Speed	1~1/10.000 sec.
Auto-Iris	Yes
Day/Night Switching	automatically removable IR Cut Filter
Digital Noise Reduction	3D Motion Compensated Noise Reduction (MCTF)
HDR	Gen3 Engine
Lens	
Focal length	2.7 to 12 mm
Focus	Auto, semi-auto, manual
FOV	Horizontal FOV 102.1° (Wide) to 31.5° (Tele), Vertical FOV 70.3° (Wide) to 22.7° (Tele)
Lens Mount	Integrated
IR Illumination	
IR Range	up to 40 m
Compression Standard	
Video Compression	H.265/H.264/MJPEG
Streaming	Up to 4 individually configurable streams in H.265/ H.264/ MJPEG Configurable resolution/ frame rate/ bandwidth LBR/ VBR/ CBR in H.265/ H.264
Single Stream 1080P H.264	NTSC: 1080P @ 60fps, PAL: 1080P @ 50fps
Single Stream 720P H.264	NTSC: 720P @ 60fps, PAL: 720P @ 50fps
Single Stream 1080P H.265	NTSC: 1080P @ 60fps, PAL: 1080P @ 50fps
Single Stream 720P H.265	NTSC: 720P @ 60fps, PAL: 720P @ 50fps
Audio	
Compression	G.711 / G.726 / AAC / LPCM
Streaming	2 way
Audio Input	Line in
Audio Output	line out
Network	
Interface	10/100Mbps Ethernet
Security	User Authentication/ HTTPS/ IP Filter/IEEE 802.1x
Supported Protocols	ARP, PPPoE, IPv4/v6, ICMP, IGMP, QoS, TCP, UDP, DHCP, UPnP, SNMP, SMTP, RTP, RTSP, HTTP, HTTPS, FTP, NTP, DDNS
ONVIF	Profile S / G / Q / T conformant
System Integration	
Analytics	Motion Detection/ Tampering/ Audio detection
Event Triggers	External Input, Analytics, Network Failure, Detection, Periodical Event, Manual Trigger
Event Actions	External output Activation, Video and audio recording to edge storage File Upload : FTP, network share and email, Notification HTTP, FTP, email

## Specifications

General	
<b>Housing</b>	Metal Body
<b>Power</b>	PoE IEEE802.3af, class 0, max 12.95 watt DC12V, max 12.95 watt AC24V, max 13.97 watt, max 25.19 VA
<b>Connectors</b>	RJ45, Alarm in x1, Alarm out x1, DC12V, AC 24V, CVBS Connector, Terminal Block
<b>Live Analog Video Output</b>	2 pin connector 75Ω, PAL class 2
<b>Storage</b>	Support for microSD/microSDHC/microSDXC card Support for recording to NAS
<b>Protection Level</b>	IP67, IK10
<b>Material</b>	Metal
<b>Operating Conditions</b>	-30°C~55°C without heater, -55°C~55°C with heater, 10%~90%, No Condensation
<b>Dimensions</b>	Ø 133.8x117.4 mm
<b>Weight</b>	760 g

### Available Model

0070-04362IR

## Accessories



0070-10016  
Internal Wall Bracket



0070-10020  
Pendant Housing



0070-10007  
Mini Gooseneck Mount



0070-10017  
In Ceiling Mount



0070-10008  
Dome Cover

## Dimensions

Unit: mm

